

Gummi hjul med stålfælg

Rubber wheels

Ø 80-280 mm

 50-350 kg



Gummi hjul shore 85A +/-3 med galvaniseret stålfælg.

Galvaniserede, rivetterede gafler med dobbelt kuglekrans i drejeled og bremsegafler med lås på både hjul og drejefunktion.

Anvendelsestemperatur: -20°C til +70°C.

Rubber wheels shore 85A +/-3 with galvanized steel rim.

Galvanized, riveted brackets with double ball race in the swivel head, brake locks both wheel and swiveling motion.

Temperature range: -4°F to +158°F.

			VARENUMMER ARTICLE NO.					MONTERINGSMÅL MOUNTING MEASUREMENTS							VARENR. ART. NO.	HJULDIMENSIONER WHEEL DIMENSIONS			
																			
SORTE / BLACK																			
80		50	6811098	6811508	6811998	6812498	6812998	108	37	100x85	80x60	8x12	12	112	481015	20	39	12	50
100		70	6811118	6811518	6812018	6812518	6813018	128	37	100x85	80x60	8x12	12	112	481035	22	39	12	70
125		100	6811138	6811538	6812048	6812548	6813038	154	37	100x85	80x60	8x12	12	129	481060	27	50	15	100
150		135	6811198	6811578	6812098	6812608	6813088	181	45	100x85	80x60	8x12	12	138	481110	27	45	20	135
160		135	6811258	6811608	6812148	6812658	6813148	197	55	140x110	105x80	11x16	16	155	481135	30	59	20	135
200		205	6811278	6811628	6812178	6812688	6813178	237	55	140x110	105x80	11x16	16	155	481230	30	59	20	205
GRÅ / GREY																			
80		50	6814098	6814508	6814998	6815498	6816008	108	37	100x85	80x60	8x12	12	112	484010	20	39	12	50
100		70	6814118	6814518	6815018	6815518	6816018	128	37	100x85	80x60	8x12	12	112	484030	22	39	12	70
125		100	6814138	6814538	6815048	6815548	6816038	154	37	100x85	80x60	8x12	12	129	484060	27	50	15	100
150		135	6814198	6814578	6815098	6815608	6816088	181	45	100x85	80x60	8x12	12	138	484110	27	45	20	135
160		135	6814258	6814608	6815148	6815658	6816148	197	55	140x110	105x80	11x16	16	155	484135	30	59	20	135
200		220	6814278	6814628	6815178	6815688	6816178	237	55	140x110	105x80	11x16	16	155	484232	30	59	20	220
250		295	-	-	6815190	6815700	6816190*	309	93	187x170	140x105	14x19	-	134	485190	35	74	20	295
280		350	-	-	6815200	6815710	6816200*	323	93	187x170	140x105	14x19	-	134	485250	40	74	20	350

* Med bagudvendt bremse

* With leading brakesystem

Alle mål er i mm

All measurements are in mm

Fås også i
antistatisk udførelse
Also available in antistatic
m/r <10⁷ Ω

