

# Polyurethanhjul, middel belastning

## Polyurethane wheels, medium duty

Ø 80-250 mm

150-750 kg



Elastisk, grå polyurethanbane shore 78A +/-3 med polyamidcenter.  
 Middelsvære, galvaniserede eller rustfrie gafler.  
 Type 1 med dobbelt kuglekrans i hærdede lejeskåle med centerbolt. Type 2 med vandtæt lejehus uden centerbolt og med smørenippel. Bremsogafler med lås på både hjul og drejefunktion.  
 Anvendelsestemperatur: -30°C til +80°C.

Elastic, grey polyurethane tread shore 78A +/-3 with polyamide centre.  
 Galvanized or stainless medium duty brackets. Type 1 with double ball race on hardened bearing shells and center bolt. Type 2 with waterproof bearing house without kingpin and with grease nipple. Brake locks both wheel and swiveling motion.  
 Temperature range: -22°F to +176°F.

Ø	Type	KG	VARENUMMER ARTICLE NO.			MONTERINGSMÅL MOUNTING MEASUREMENTS						VARENR. ART. NO.	HJULDIMENSIONER WHEEL DIMENSIONS				
80		150	6467410	6467540	6467710	120	40	105x85	80x60	9x16	120	447582	34	40	12	150	2
80		150	6467412	6764542	6467712	125	47	100x84	80x60	9	113	447582	34	40	12	150	1
100		200	6467428	6467548	6467728	135	47	100x84	80x60	9	114	447622	34	40	12	200	1
100		200	6467429	6467549	6467729	140	45	105x85	80x60	9x16	120	447622	34	40	12	200	2
125		250	6467432	6467557	6467732	162	47	100x84	80x60	9	128	447690	40	50	15	250	1
125		250	6467435	6467560	6467735	165	45	105x85	80x60	9x16	120	447690	40	50	15	250	2
125		250	6467443	6467563	6467743	165	61	132x110	105x80	12	158	447690	40	50	15	250	1
125		250	6467445	6467565	6467745	178	50	135x110	105x80	11x16	146	447690	40	50	15	250	2
150		350	6467448	6467578	6467748	190	45	105x85	80x60	9x16	120	447750	45	50	20	400	2
150		400	6467459	6467589	6467759	195	60	132x110	105x80	12	157	447775	45	60	20	400	1
150		400	6467465	6467595	6467765	205	50	135x110	105x80	11x16	146	447775	45	60	20	400	2
160		400	6467487	6467617	6467777	200	60	132x110	105x80	12	158	447792	45	60	20	400	1
160		400	6467492	6467622	6467782	210	50	135x110	105x80	11x16	146	447792	45	60	20	400	2
200		600	6467508	6467638	6467798	250	55	135x110	105x80	11x16	146	447830	50	60	20	600	2
200		600	6467507	6467637	6467797	242	59	132x110	105x80	12	158	447830	50	60	20	600	1
250		700	6467510	6467640	6467800*	300	70	135x110	105x80	11	145	447910	60	75	20	750	2
250		750	6467512	6467642	6467802*	309	64	200x160	160x120	15	135	447910	60	75	20	750	1
<b>STAINLESS</b>																	
80		150	6483410	6483540	6483710	120	40	105x85	80x60	9x16	120	447583	34	40	12	150	2
100		200	6483422	6483552	6483722	140	45	105x85	80x60	9x16	120	447623	34	40	12	200	2
125		250	6483430	6483560	6483730	165	45	105x85	80x60	9x16	120	447691	40	50	15	250	2
125		250	6483435	6483565	6483735	178	50	135x110	105x80	11x16	146	447691	40	50	15	250	2
150		350	6483445	6483575	6483745	190	45	105x85	80x60	9x16	120	447751	45	50	20	400	2
150		400	6483455	6483585	6483755	205	50	135x110	105x80	11x16	146	447777	45	60	20	400	2
160		400	6483475	6483605	6483775	210	50	135x110	105x80	11x16	146	447795	45	60	20	400	2
200		600	6483480	6483610	6483780	250	55	135x110	105x80	11x16	146	447835	50	60	20	600	2

\* Med bagudvendt bremse  
 \* With leading brakepedal

Alle mål er i mm  
 All measurements are in mm