

Alu / polyurethan hjul

Alu / polyurethane wheels

Ø 80-250 mm

150-1.100 kg



Polyurethanbane shore 92A +/-3 vulkaniseret på aluminiumscenter.

Fås også med blødere bane, shore 78 +/-3.

Anvendelsestemperatur: -30°C til +80°C.

Polyurethane tread shore 92A +/-3 vulcanised on aluminum centre.

Also available with softer tread, shore 78 +/-3.

Temperature range: -22°F to +176°F.

							VARENUMMER ARTICLE NO.						
							Ø10	Ø12	Ø15	Ø17	Ø20	Ø25	UDEN LEJER WITHOUT BEARINGS
80	20	20	32x13	38	68	150	-	455602	455604	-	-	-	455600
100	30	39	35x12	42	87	200	455612	-	455614	455616	-	-	455610
125	30	39	35x12	42	110	250	455622	-	455624	455626	-	-	455620
125	45	60	47x17	55	100	350	-	-	-	455632	455634	455636	455630
150	40	49	47x17	55	134	400	-	-	-	455662	455664	455666	455660
160	50	60	47x17	55	140	600	-	-	-	455682	455684	455686	455680
160	50	60	52x17	62	140	600	-	-	-	-	-	-	455690
175	40	49	47x17	55	157	550	-	-	-	455722	455724	455726	455720
180	50	60	47x17	60	140	700	-	-	-	455742	455744	455746	455740
200	50	60	47x17	60	184	800	-	-	-	455802	455804	455806	455800
200	50	60	52x17	60	184	800	-	-	-	-	-	-	455810
225	60	70	47x17	58	190	1000	-	-	-	455842	455844	455846	455840
250	60	60	52x17	62	228	1100	-	-	-	-	455872	455874	455870

Alle mål er i mm
All measurements are in mm

